

SWIMWARE Alphanumeric Scoreboards



IST's SWIMWARE Alphanumeric Scoreboards are available in one line to 10 lane displays with 16 or 32 bright red LED characters per line.

TIMEWARE for Windows and Hy-Tek's MEET MANAGER Software drive the board for swimming. Before an event, the top line scrolls the event name and number. Lane lines display the team code and name of swimmers. Names remain on the board until the first split, but team codes are displayed throughout the event. All 50 splits are shown, along with the cumulative time (32 character boards show teams, names, 50 and cumulative splits).

During diving events, the board displays the diver's team, name, current score and place, DD's, judges' awards, the score for that dive, the new total score and the current leading score.

With POLOWARE for Windows Water Polo Software, the board displays the period, shot clock, exclusion clock, and home and guest scores. As events occur (scores, penalties, exclusions) the cap number and name of the player are also shown.

Use WORKWARE for Windows to run a different workout clock on each line of the scoreboard, with an interval counter and description of the set.

Software packages include Message Board function to turn SWIMWARE Alphanumeric Scoreboards into information centers. The top line scrolls up to 1000 characters, and lane lines can show fixed or alternating messages.

All boards include a team or sponsor logo of your design. Like all IST products, SWIMWARE Alphanumeric Scoreboards have a 5 year warranty.

Shows More Information Than Any Other Aquatic Scoreboard

- Bright Red LED Display
- Protective Lens
- Modular Construction
- Indoor or Outdoor
- Very Low Power Use
- Message Capability
- 5-Year warranty

IST

International Sports Timing
3286 Kentland Ct., S.E.
Grand Rapids, MI 49548
Phone: 800/835-2611
Fax: 616/247-0086
Web: www.istime.com
Email: info@istime.com

Specifications

Control Software

- IST's TIMEWARE, POLOWARE or WORKWARE for Windows

Physical

- 1 line to 10 lane boards
- Each line 12" H x 8' W (16' for 32 character) x 4" D
- 13" W lane number panels
- Custom logo panel included
- Weight: 50 pounds per line
- Aluminum - black powder coat finish with red Plexiglas lens
- 16 or 32 character display of red Light Emitting Diodes (high intensity LED's for outdoor).

Electrical

- One 110V 15 amp (min.) outlet (2 for 32 character boards)
- Maximum load requirement is 4.4 Amps (8.8 for 32 char.)
- Data communication via RS485
- Conformal coated electronics

Environmental

- Operating range: 0° to +55°C
- Storage range: -55° to +85°C
- Operating humidity <=90% non-condensing